

## VC-04 Color Video Camera

### Product Overview

The TDK VC-04 Color Video Camera is a high performance CCD specifically designed for remote monitoring of equipment under EMC testing. The camera is also ideal for wide angle anechoic chamber monitoring, shielded access control, and test action archiving.

**Designed for EMC Testing** The VC-04 is designed to operate in the harsh environments required by EMC testing. The camera is housed in an EMI hardened protective case, and the control and video signals use fiber optics to prevent interference caused by high electromagnetic fields present during EMC testing.

**Full-Featured** The high-resolution VC-04 is remotely focused, positioned, and zoomed using the TDK SI-300CC controller. The camera is available in both NTSC and PAL versions.



**The TDK VC-04 Color Video Camera is designed specifically for remote monitoring of equipment during EMC testing in a shielded room or anechoic chamber.**

### Camera Features

- 1/4" CCD; high resolution; NTSC and PAL versions
- EMI shielded to >200 V/m (DC to 18 GHz); Shielded 12 V DC or universal AC adapter operated
- Pan/tilt mechanism
- Remote control for pan/tilt, focus, zoom, iris control
- Computer control with IEEE-488 option
- Audio option provides both audio and visual monitoring

### VC-04 Video Camera System Components

- One VC-04 Color Video Camera
- SI-300CC Camera Controller capable of controlling up to four VC-04 cameras
- A 20" LCD monitor
- One set of 25m fiber optic cables
- Either AC power or DC battery pack
- Permanent sturdy fixture

### Options

- Built-in audio
- VCMS-150R Video Camera Monopod Stand
- VCWM Video Camera Wall Mount
- AC power or DC battery pack

# VC-04 Color Video Camera

## Overall Dimensions

With pan/tilt unit:	10.5" H x 6.2" D x 3.0" W (26.7 cm x 15.8 cm x 7.6 cm)
Without pan/tilt unit:	5.0" H x 6.2" D x 3.0" W (12.7 cm x 15.8 cm x 7.6 cm)

## Electrical/Environmental Specifications

Image:	1/4" IT CCD Active Picture Elements
NTSC:	768 (H) x 494 (V)
PAL:	752 (H) x 582 (V)
Resolution:	
NTSC:	470 (H) x 350 (V)
PAL:	460 (H) x 400 (V)
Signal to Noise Ratio:	min 49 dB
Video Output:	Optically encoded NTSC or PAL
Color Balance:	Automatic Synchronization
Operating temperature:	0° to +40° C
Storage Temperature:	-10° to +50° C

## Motor Box Specifications

Houses the motors which power the pan/tilt mechanism.	
Power:	110-220 VAC / 12 VDC
Dimensions:	7.0" H (including mount) x 7" D x 4.7" W (18 cm x 12 cm x 7.6 cm)
Construction:	Painted steel

## Optical Capabilities

Focal Length:	3.5 – 91 mm
Zoom:	26x Optical zoom 12x Digital zoom
Angular Field of View:	55° wide; 2.3° telephoto
Minimum Object Distance:	35 mm (wide); 800 mm (telephoto)
Angle of Pan/Tilt:	Pan: +/- 150° degrees Tilt: +/- 30° digress
Fiber Optic Cable:	62.5 u glass fiber
Iris Control:	Manual and Automatic
Minimum Illumination:	0.7 lux

## Ordering Information

Product:	Video Camera
Model Number:	VC-04
Warranty:	1 year

**To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:**

### TDK RF Solutions Inc.

1101 Cypress Creek Rd.  
Cedar Park, Texas 78613 USA  
Phone: 1-512-258-9478  
Fax: 1-512-258-0740  
E-mail: [info@tdkrf.com](mailto:info@tdkrf.com)  
World Wide Web: [www.tdkrfsolutions.com](http://www.tdkrfsolutions.com)



[www.tdkrfsolutions.com](http://www.tdkrfsolutions.com)

To learn more about TDK's wide range of innovative test products, solutions and services visit [www.tdkrfsolutions.com](http://www.tdkrfsolutions.com)

Copyright © TDK RF Solutions Inc. All rights reserved. Specifications subject to change without notice.

Rev. 2011-08-02